

Determination D0113EN	Edition: 7 Valid from: 2026-01-26 Review: 2029-01-23	Owner: PEQAC	Everlence
Approval List LO for Gaseous Fuel Operation SAE 40			

Applicable for Everlence four stroke medium-speed large bore gas engines (type 35/44, 51/60) and for PC type gas engines of the Pielstick brand

Company	Oil brand	BASE NUMBER (mg KOH/g)
Addinol	Eco Gas 4000 XD ¹⁾	7.3
ExxonMobil	Pegasus 710 Pegasus 805	6.5 6.2
Fuchs Petrolube	Fuchs Titan Ganymet Ultra LA	5.5
Shell	Mysella S3 N40 Mysella S5 N40 ¹⁾	5.0 4.5
Chevron Texaco Caltex	HDAX 5200 Low Ash SAE 40 ¹⁾	4.2
Repsol	Long Life Gas 4005 ¹⁾	5.1
TotalEnergies	Aurelia LNG ¹⁾ Aurelia NGX 40 ¹⁾ Nateria MP 40 ¹⁾ Nateria MWX 40 ¹⁾	4.6 7.3 4.6 7.3

¹⁾Mandatory for CHP cycle applications

Definition “Gaseous Fuels”: NG, LNG, synthetic gas, bio gas according to Everlence Specification for Gaseous Fuels (GF)

We do not assume any responsibility for difficulties that might be caused by these oils.

For Pielstick engines, not all recommended lube oils are listed in this document.

For more information, please contact your Pielstick technical correspondent.